

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

Auto Magic

Professional Car Care[®]

1. Identification

Product identifier used on the label:

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Other means of identification

Synonyms: No data available

Chemical Family: ALCOHOL

Recommended use of the chemical and restrictions on use: Dye

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Chemical Manufacturer /
Importer / Distributor: ITW Evercoat
a division of Illinois Tool Works Inc.
1275 Round Table Drive
Dallas, TX 75247

Emergency phone number: CHEMTREC: 1-800-424-9300
CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard
Symbols:



GHS Classification:

Serious Eye Damage/Eye Irritation Category 1
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1B
Skin Corrosion/Irritation Category 2
Reproductive Toxicity Category 2
Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 2
Hazardous to the aquatic environment - Acute Category 2
Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Hazardous to the aquatic environment - Chronic Category 3

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

GHS Signal Word:

Danger

GHS Hazard Statements:

Causes skin irritation.

Causes serious eye damage.

May cause drowsiness or dizziness.

May cause genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Toxic to aquatic life.

Harmful to aquatic life with long lasting effects.

GHS Precautionary Statements:

Safety Precautions:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

First Aid Measures:

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Immediately call a POISON CENTER/doctor

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

If skin irritation occurs: Get medical advice/attention.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

Hazards not otherwise classified:

No data available

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

3. Composition/information on ingredients

Chemical Component:	CAS number and other unique identifiers	% (or range) of ingredient
Acetone	67-64-1	15 - 40
Petroleum gases, liquefied	68476-86-8	10 - 30
Toluene	108-88-3	10 - 30
Methyl ethyl ketone	78-93-3	5 - 10
Xylene	1330-20-7	1 - 5
n-Butyl alcohol	71-36-3	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

- Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician. Flush eyes gently with water for at least 15 minutes, lifting upper & lower eye lids. Seek immediate medical attention.
- Skin Contact:** Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water. Wash affected area thoroughly with soap and water. Seek medical advice if symptoms persist Wash clothing before reuse. Thoroughly wash or discard clothing and shoes before reuse.
- Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately. If symptoms develop, immediately move individual away from exposure and into fresh air. Get medical attention immediately. Keep the victim warm and quiet. If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice.
- Ingestion:** Corrosive. Do not induce vomiting! Drink one glass of water followed by milk if available. Seek medical attention immediately and give the medical care provider with this MSDS. Call a physician or poison control center immediately. Do not induce vomiting unless directed to do so by medical personnel. If individual is drowsy or unconscious, do not give anything by mouth; place

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

individual on left side with head down. If possible, do not leave individual unattended. Induce vomiting as a last measure. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

Most important symptoms/effects, acute and delayed:

Most important symptoms/effects (Acute): No data available

Most important symptoms/effects (Delayed): No data available

Indication of immediate medical attention and special treatment needed, if necessary: No additional first aid information available

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water spray or fog may also be effective for extinguishing if swept across the base of the fire. Water can also be used to absorb heat and keep exposed material from being damaged by fire. Regular foam Carbon dioxide Dry chemical

Unsuitable extinguishing media: No data available

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

Fire and/or Explosion Hazards: Vapors may be ignited by heat, sparks, flames or other sources of ignition at or above the low flash point giving rise to a Class B fire. Vapors are heavier than air and may travel to a source of ignition and flash back

Hazardous Combustion Products: Toxic and corrosive gases,, Carbon dioxide, Carbon monoxide, Hydrocarbons, Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters: Do not enter fire area without proper protection including self-contained toxic breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Flammable component(s) of this material may be lighter than water and burn while floating on the surface. Use water spray/fog for cooling. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

protective equipment.
Flammable component(s) of this material may be lighter than water and burn while floating on the surface.
Use methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill. Evaporation of volatile substances can lead to the displacement of air creating an environment that can cause asphyxiation.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area. Activate available exhaust ventilation equipment in the immediate spill area. All personnel in the area should be protected as in Section 8. Avoid breathing vapors. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container.

7. Handling and storage

Precautions for safe handling:

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. All hazard precautions given in the data sheet must be observed. Do not get in eyes, on skin and clothing Wash hands before eating Use with adequate ventilation Avoid breathing vapors or mists. Do not take internally. Keep container closed when not in use. Keep out of the reach of children. Use spark-proof tools and explosion-proof equipment Follow all protective equipment recommendations provided in Section VIII. Minimize dust generation and accumulation

Conditions for safe storage, including any incompatibilities

Conditions for safe storage:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Store in a cool dry place For maximum product quality, avoid prolonged storage at

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

temperatures above 75 °F (25 °C). Keep away from heat, sparks, and flame Store in a tightly closed container Avoid contact with incompatible materials. Keep away from sources of ignition
Hydrogen peroxide Strong oxidizing agents Strong acids Acids
Aluminum alloys Ammonia

Materials to Avoid/Chemical Incompatibility:

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical Component	OSHA PEL	ACGIH TLV-TWA	ACGIH STEL
Acetone	1000 ppm	500 ppm	750 ppm
Toluene	100 ppm	100 ppm	No data available
Methyl ethyl ketone	590 mg/m ³	590 mg/m ³	885 mg/m ³
Xylene	100 ppm	100 ppm	150 ppm
n-Butyl alcohol	100 ppm	No data available	No data available

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits. Explosion proof exhaust ventilation should be used.

Individual protection measures, such as personal protective equipment:

Eye Protection:

Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available. Splash proof chemical goggles are recommended to protect against the splash of product. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin Protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

Respiratory Protection:

Respiratory protection will be required when handling this product. Use respirators only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors. Respirators should be selected

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2-1992). A written respiratory protection program, including provisions for medical certification, training, fit testing, exposure assessments, maintenance, inspection, cleaning, and convenient, sanitary storage must be implemented. NIOSH approved air purifying respirator with organic vapor cartridge and HEPA filter. Air purifying respirators should not be used in oxygen deficient or IDLH atmospheres

Other Protective Equipment:

Splash proof chemical goggles are recommended to protect against the splash of product. Wear splash-proof safety goggles if material could be misted or splashed into eyes. Protective gloves and proper clothing should be worn to prevent skin contact. Gloves should be made of neoprene or natural rubber. To prevent repeated or prolonged skin contact, wear impervious clothing and boots

9. Physical and chemical properties

Appearance (physical state, color, etc.):

Appearance (physical state):

Liquid with propellant

Color:

Black

Odor:

Aromatic solvent odor

Odor threshold:

No data available

pH:

No data available

Melting Point/Freezing Point (°C):

No data available

Initial Boiling Point and Boiling Range (°C):

56

Flash Point (°C):

No data available

Evaporation Rate:

2-10 (n-Butyl acetate = 1)

Flammability (solid, gas):

No data available

Upper/lower flammability or explosive limits:

Upper Flammable/Explosive Limit (%):

12.8

7.0 %

11.4

7

11.2 %

Lower Flammable/Explosive Limit (%):

1

Vapor Pressure:

No data available

Vapor Density:

No data available

Relative Density:

0.25

Solubility(ies):

Insoluble

Partition coefficient: n-octanol/water:

1.36

Auto-ignition Temperature (°C):

No data available

Decomposition Temperature:

No data available

Viscosity:

No data available

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

10. Stability and reactivity

Reactivity:	No data available
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	No data available
Conditions to avoid (e.g., static discharge, shock, or vibration):	Sparks, open flame, other ignition sources, and elevated temperatures. Contamination
Incompatible materials:	Hydrogen peroxide Strong oxidizing agents Strong acids Acids Aluminum alloys Ammonia
Hazardous decomposition products:	Carbon dioxide Carbon monoxide Hydrocarbons Carbon dioxide, Carbon monoxide

11. Toxicological information

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact):	Ingestion, Skin contact, Eye contact, Absorption, Skin contact, Eye contact, Inhalation
Symptoms related to the physical, chemical and toxicological characteristics:	No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Irritation:	Can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Excessive inhalation of vapors may cause nasal and respiratory irritation, acute nervous system depression, fatigue, weakness, nausea, headache and dizziness. Airborne overexposure well above the PEL may result additionally in eye irritation, headache, chemical bronchitis, asthma-like findings or pulmonary edema. Harmful! Can cause severe irritation or burns and lung inflammation. Central nervous system effects such as dizziness, weakness, fatigue, nausea, headache, and unconsciousness are possible. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs). Can cause mechanical irritation if dusts are generated.
Inhalation Toxicity:	Harmful! Can cause systemic damage (see "Target Organs")
Skin Contact:	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Harmful if absorbed through the skin. May cause severe irritation and systemic damage. Causes skin irritation. Contact may cause irritation and possible dermatitis or sensitization. Symptoms may include redness, burning, drying and cracking of skin, and skin burns

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

Eye Contact:	Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible. Contact with liquid or vapor may result in irritation, redness, tearing, and blurred vision.
Ingestion Irritation:	Corrosive to tissue. Can cause severe and permanent damage to mouth, throat, stomach. Aspiration may lead to lung damage. Causes gastrointestinal tract irritation, nausea, vomiting, diarrhea and possible ulcerations to mucous membranes. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal. May also cause effects on the liver and kidneys. Harmful if swallowed.
Ingestion Toxicity:	Harmful if swallowed. May cause systemic poisoning.
Long-Term (Chronic) Health Effects:	
Carcinogenicity:	May cause cancer. Not listed by ACGIH, IARC, NIOSH, NTP OR OSHA.
Reproductive and Developmental Toxicity:	Suspected of damaging fertility or the unborn child.
Mutagenicity:	May cause genetic defects.
Inhalation:	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness. Harmful! Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Organs")
Skin Contact:	Upon prolonged or repeated contact, can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption:	Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause severe irritation and systemic damage.

Numerical measures of toxicity (such as acute toxicity estimates)

Component Toxicology Data

Chemical Component	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	Oral LD50 Rat 5800 mg/kg	Dermal LD50 Rabbit 20000 mg/kg	Inhalation LC50 (4h) Rat > 16000 ppm
Toluene	Oral LD50 Rat 5000 mg/kg		Inhalation LC50 (4h) Rat 4000 ppm
Methyl ethyl ketone	Oral LD50 Rat 2737 mg/kg		Inhalation LC50 Rat 23500 mg/m3
Xylene	Oral LD50 Rat 4300 mg/kg		Inhalation LC50 (4h) Rat 5000 ppm
n-Butyl alcohol	Oral LD50 Rat 790 mg/kg		Inhalation LC50 (4h) Rat 8000 ppm

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

Whether the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No data available	N	N	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Toxic to aquatic life. Toxic to aquatic life with long lasting effects. This material is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits. Highly/very toxic to fish and other water organisms.

Persistence and degradability:

No data available

Bioaccumulative potential:

No data

Mobility in soil:

No data available

Other adverse effects (such as hazardous to the ozone layer):

No data available

Ecological Toxicity Data

Chemical Component	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Acetone	Aquatic EC50 (48h) Daphnia 10294 - 17704 MG/L		Aquatic LC50 (96h) Rainbow Trout 4740 - 6330 MG/L
n-Butyl alcohol	Aquatic EC50 (48h) Daphnia 1897 - 2072 MG/L		Aquatic LC50 (96h) 100 - 500 MG/L
Xylene			Aquatic LC50 (96h) 7.711 - 9.591 MG/L

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging

Description of waste residues:

Spent or discarded material is a hazardous waste.

Safe Handling of Waste:

This material as supplied, if discarded, would be regulated as a hazardous waste under RCRA (40 CFR 261).

Waste treatment methods (including packaging):

Dispose of by incineration following Federal, State, Local, or Provincial regulations.

Waste Disposal Code(s):

D001 U002 acetone

Safety Data Sheet

Product Name: Vinyl plastic carpet dye charcoal gray

Product identifier: 00245 - 00279

Revision Date: 08-18-2016

Replaces:

14. Transport information

UN number: 1950
UN proper shipping name: AEROSOLS
Transport hazard class(es): 2.1
Packing group: No data available

The shipper is responsible for following all applicable regulations. The transportation classification provided is based on ITW Evercoat original packaging, which is suitable for domestic ground transport only.

15. Regulatory information

Safety, health and environmental regulations specific for the product in question

TSCA Status: The intentional ingredients of this product are listed.

Regulated Components

Chemical Component	CAS number and other unique identifiers	CERCLA	SARA EHS	SARA 313	California Prop 65
Acetone	67-64-1	N	N	Y	N
Toluene	108-88-3	N	N	Y	Y
Methyl ethyl ketone	78-93-3	N	N	Y	N
n-Butyl alcohol	71-36-3	N	N	Y	N
Xylene	1330-20-7	N	N	Y	N

16. Other information, including date of preparation or last revision.

Revision Date: 08-18-2016

Revision Number: 7

Disclaimer: NOTICE: The information accumulated herein is believed to be correct as of the date issued from sources, which are believed to be accurate and reliable. Since it is not possible to anticipate all circumstances of use, recipients are advised to confirm, in advance of need, that the information is current, applicable and suitable to their circumstances