



## Product Technical Bulletin

**PRODUCT NAME:**

Clay Magic® Polymer Detailing Clay Bar

**PART #:**

CM3200  
(Polymer Clay)

**PACKAGE:**

200 gram bar

**PRODUCT CATEGORY:**

Surface Preparation

**COLOR:**

White

**SCENT:**

N/A

**ABRASIVENESS:**

0.5 out of 10 (10 is highest amount of abrasive)

**PRODUCT DESCRIPTION:**

**Clay Magic® Polymer Clay** is an advanced clay that contains an embedded polymer that helps to glide the bar over surfaces better than ever. This Clay is ideal for vehicles that have been Ceramic Coated or have extremely Soft Clear Coat. These embedded polymers, paired with a proper Clay Lubricant give you the ability to perform mechanical decontamination on coated and clear coat surfaces without damaging the finish. Polymer Clay will leave you with a decontaminated surface without the marring and side effects of more aggressive alternatives, Polymer Clay is softer than other clay bars, which makes it easier than ever to mold and form. It removes harmful surface contaminants such as paint overspray, tree sap, bug residue, industrial fallout, bird droppings, and other stubborn dirt. Polymer Clay is safe on all paint, coated, chrome, glass, fiberglass, and plastic. Use it with Clay Lube.

**DIRECTIONS:**

Form Clay Magic® into an oval shape. Spray Clay Magic® Clay Lube onto a 3'x3' section of a clean, cool, and dry surface. Gently rub the clay bar over the area using a back-and-forth motion in 5 to 6 passes. Wipe the surface dry. To clean the clay bar, simply fold it in half and reshape into an oval shape. Store the clay bar in a clay container or plastic baggie with a light spray of lubricant. **DISCARD BAR IF DROPPED ON THE GROUND.**

**SURFACE APPLICATIONS:**

Refinished paint, factory paints, clear coats, acrylics, enamels, and lacquer paints. It can also be used on glass, chrome, fiberglass, plastic, ceramic coatings and many other smooth hard surfaces for contamination and paint overspray removal.

**HELPFUL TIPS:**

Always make sure the surface you intend to clay is thoroughly washed, dried, and cool. Fold the clay frequently to ensure clean clay is used. It is best to fold the clay after each main body panel is completed. Most of the contamination removal is going to be on the upper portions of the vehicle (above the side moldings). Do not use clay without a clay lubricant. The lubricant helps glide the clay and loosen imbedded surface debris. Do not use the clay if dropped on the ground. This collected dirt may add surface scratches.

**SAFETY & HANDLING:**

Safety Data Sheets can found online at [automagic.com](http://automagic.com)



## Product Technical Bulletin

