



## Product Technical Bulletin

**PRODUCT NAME:**

XP Polish™

**PART #:**

88A

88

**PACKAGE:**

16 oz

Gallon

**PRODUCT CATEGORY:**

Polishes & Glazes

**COLOR:**

White

**SCENT**

N/A

**ABRASIVENESS:**

7 out of 10 (10 is highest amount of abrasive)

**PRODUCT DESCRIPTION:**

XP Polish™ is a moderately aggressive leveling polish designed to eliminate car wash scratches and light-to-medium oxidation. Specially blended with advanced polymers to increase durability. May be applied by hand or a variable speed polisher. Works well with wool or foam cutting pads. VOC Compliant.

**DIRECTIONS:**

- Shake well.
- Variable Speed Polisher: Starting with a two foot by two foot area apply product and polish to high gloss.
  - **Wool Pads** – Recommended polisher speed is 1500 - 1800 RPM.
  - **Foam Pads** – Recommended polisher speed is 1200 - 1500 RPM.
- Orbital Polisher - Work in a two foot by two foot area until desired gloss is achieved.
- Hand application - Use a wax applicator in overlapping, circular motions. Allow to haze, and then remove with a soft, terry towel.

**SURFACE APPLICATIONS:**

For leveling clear coat, single stage, acrylic, lacquer, enamel and powder coat paints

**ADDITIONAL USES:**

Excellent on RVs, boats, motorcycles, ATVs, and other painted surfaces.

**HELPFUL TIPS:**

Use Clay Magic® detailing clay prior to applying XP Polish™ for the best possible performance. Follow with an Auto Magic® wax or polymer finish for added protection and gloss. Use XP Polish™ on cool surfaces.

**SAFETY & HANDLING:**

Safety Data Sheets can found online at [automagic.com](http://automagic.com)